

## RP23



A tested S.E. Neoprene compression smoke and weather seal for broad butt hinged doors. Its aluminium carrier is sturdy and slotted for adjustment with concealed fixings. It can be mitred or butt jointed.

RP23 is quick and easy to install onto door stops around the jamb and head and can be fitted without removing the door. A built up sill across the foot of the door, similar in profile to the stops on the door jambs, will be required for bulkhead sealing applications.

**Location** Head and jambs on single or double broad butt hinged doors (or bulk head applications).

**Min/Max Gap** 0mm/7mm.

**Seal Sizes** Available in stock lengths or door set sizes.

**Standard Finish** Aluminium anodised 15 microns. Satin Clear (Silver) or Bronze finish.

**P.E. Paint** (extra cost). Is a two pack polyester enamel colour match finish which is equal to or exceeds powdercoat finish.

**Fixing Method** Zinc plated, cross recess head S.T. screws of the appropriate size are supplied.

**Seal Material** Neoprene (self extinguishing) black.

**Replacement Seal** RP323.

**Used in conjunction**

Raven threshold plates, door bottom seals, astragal seals.

### Approvals

**Fire & Smoke** AUS/NZ: Tested to AS 1530.4 & AS/NZS 1905.1.

UK/EU: Tests above are similar to BS EN 1634.1, BS 476 Part 20 & 22.

Conforms to **BS5588 Pt1** when tested in accordance with **BS476 Pt31.1**.

**Acoustic** AUS/NZ: Conforms to BCA Sec. F5.5. Tested to AS 1191, AS 1045, AS/NZS 1276.

UK/EU: Tested to BS EN ISO140.3 (similar to BS EN ISO 717.1, BS 2750, BS 5821).

