

RP35 Si

M



RP35 Si is a medium duty automatic door bottom seal which is spring loaded to lift clear of the sill as soon as the door leaf is opened. Acoustically designed for face mounted and semi-morticed applications. It is operated automatically by pressure against the door jamb on its adjustable strike block.

Min/Max 1mm/13mm.

Location Solid core single and double, broad butt hinged doors.

Seal Sizes

1220mm, 1070mm, 920mm, 820mm, 600mm, 380mm to 295mm (min). Seals cut back to exact size.

Standard Finish Aluminium anodised 15 microns. Satin Clear (Silver) or Bronze finish.

Fixing Method

Zinc plated, cross recess head S.T. screws and colour matched escutcheon plates supplied.

Adjustment Has adjustment strike block screw for sealing action adjustment.

Seal Material

Silicon rubber (SE) (grey) with rigid PVC cover strip (grey).

Replacement Seal RP308 Si.

Approvals

Acoustic UK/EU: Conforms to Approved Document E. Tested to BS EN ISO 140.3, BS EN ISO 717.1, BS 2750, BS 5821.

Fire & Smoke AUS/NZ: Conforms to BCA Spec. C3.4. Tested to AS 1530.4, AS/ NZS 1905.1 & AS/NZS 1530.7.

UK/EU: Conforms to Approved Document B. Tested to ISO CD 5925-1 (similar to BS EN 1634.1, BS 476 Part 20 & 22, Sec. 31.1).

Durability tested to over 1,000,000 operating cycles without failure.

